

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

7:13.1

← missing sentence

Sub
A1 }

BACKGROUND OF THE INVENTION

5 The present invention relates to a screening housing for microwave circuits. More particularly, it relates to such a screening housing with a plurality of chambers which are screened from one another and which accommodate circuit units to be oppositely electromagnetically coupled.

10 Conventionally, a multi-chamber housing which must accommodate a plurality of microwave circuits screened from one another in a high frequency type manner is produced by milling of the individual chambers from a massive metal body. One of such screening housings is disclosed for example in the German document DE 35 04 726 C1. The manufacture of such a housing with several high frequency-tight chambers is very expensive.

15 Another German patent document DE 43 19 965 A1 discloses a housing with separating joints provided for example between the cover and the housing walls, and sealing profiles inserted in the separating joints and composed of an elastic polymer with embedded metal particles.

SUMMARY OF THE INVENTION

Accordingly, it is an object of the present invention to provide a screening housing of the above mentioned type which avoids the disadvantages of the prior art.

5 More particularly, it is an object of the present invention to provide a screening housing of the above mentioned general type which can be produced with lower expenses.

IND A2 }
10 In keeping with these objects and with others which will become apparent hereinafter, one feature of present invention resides, briefly stated in a screening housing for microwave circuits, in which on the inner side of the cover which closes the housing, a substrate is arranged of a polymer with embedded metal particles, and webs are provided on the substrate which together with the placed cover form the separating walls between the chambers.

15 The substrate with the webs which form the chambers can be cast on the inner side of the cover. Any structure of the substrate with webs can be made without high expenses. The substrate ^{made} from a polymer with the

embedded metal particles not only performs a screening function, but also dampens simultaneously undesirable resonance frequency in the chambers.

a The material of the housing, ~~in particular polymer with the~~

a ~~embedded metal particles~~ can be a silicone mass filled with iron powder.

5 The novel features which are considered as characteristic for the present invention are set forth in particular in the appended claims. The invention itself, however, both as to its construction and its method of operation, together with additional objects and advantages thereof, will be best understood from the following description of specific embodiments when read in connection with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a view showing an open screening housing with its interior, in accordance with the present invention; and

Figure 2 is a view showing the same screening housing from an inner side of its cover.

5

a

a

10

a

5

10

15

Several webs 5, 6, 7, 8 are provided on the face of the substrate 4 which faces toward the interior of the housing 1. When the cover 3 is placed on the housing, the separating walls 5, 6, 7, 8 together with the cover 3 form the individual chambers inside the screening housing. As shown in the embodiment of Figure 2, the webs 5, 6, 7, 8 can have an arbitrarily complicated structure.

The substrate 4 with the webs 5, 6, 7, 8 can be manufactured in a simple manner by casting with a mold on the inner side of the cover 3. The webs 5, 6, 7, 8 abut in a form-locking manner against the bottom of the chamber 2 when the cover 3 is placed on the housing. Additionally, they can be provided with throughgoing openings 9, 10, 11 for connecting conductors between the individual circuit units.

The webs 5, 6, 7, 8 which are composed of polymer with embedded metal particles have not only the function of screening walls but also dampen simultaneously the undesired resonance frequencies in the chamber.

It will be understood that each of the elements described above, or two or more together, may also find a useful application in other types of constructions differing from the types described above.

While the invention has been illustrated and described as embodied in screening housing for microwave circuits, it is not intended to be limited to the details shown, since various modifications and structural changes may be made without departing in any way from the spirit of the present invention.

5

Without further analysis, the foregoing will so fully reveal the gist of the present invention that others can, by applying current knowledge, readily adapt it for various applications without omitting features that, from the standpoint of prior art, fairly constitute essential characteristics of the generic or specific aspects of this invention.

What is claimed as new and desired to be protected by Letters Patent is set forth in the appended claims.